

# Jumbo Reels



## DESCRIPTION

Jumbo Reels are manufactured from aluminium alloy with a thickness of between 9 and 40 microns. The foil retains the typical features and benefits associated with aluminium products, i.e. low mass, suitability for direct contact with foodstuffs, remaining chemically stable when exposed to air and excellent barrier properties.

## TYPICAL APPLICATIONS

- The Jumbo Reel foil is supplied for re-winding into domestic lengths and is utilised in the retail and catering industries for the protection, treatment and wrapping of food and foodstuffs.

## STANDARD MANUFACTURED MATERIAL

|                                      |                                    |
|--------------------------------------|------------------------------------|
| Material in Accordance with EN 573-3 | Temper in Accordance with EN 546-2 |
| EN AW-8011A [Al FeSi(A)]             | O                                  |

## STANDARD DIMENSIONS

|                   |               |
|-------------------|---------------|
| Thickness<br>[µm] | Width<br>[mm] |
| 9 - 40            | 280 - 1000    |

Dimensional tolerance in accordance with EN 546-3.

Mechanical properties in accordance with EN 546-2.

The chemical composition of this product is in accordance with EN602 and the lubricants applied during the rolling process conform to (FDA). This specification should be considered when evaluating the products suitability for use in direct contact with food or foodstuffs.

The foil is supplied with a steel core of 70 mm, 76 mm or 150 mm.

**For deliveries of material not specified above please contact one of our Key Account Managers to discuss your individual needs.**

